



ICG<sup>®</sup> Drum Scanners

**ICG<sup>®</sup> 370HS**



## TECHNICAL DATA

<b>Media</b>	Transparency, colour negative, reflection copy, monochrome, linework, screened film separations (optional)	
<b>Enlargement range</b>	20-6000% continuously variable	
<b>Resolution</b>	Up to 12000 dpi (472.5 p.p.m.m.)	
<b>Density range</b>	0 to 4D	
<b>Image file format</b>	TIFF or DCS	
<b>Technology</b>	3 precision photomultipliers and non-fade dichroic filters	
<b>Lamp</b>	Quartz-halogen	
<b>Drums</b>	A3+ external drum	Maximum scan area: 476 x 320 mm (18.7 x 12.6 inches)
	SlickMount internal drum	Maximum scan area: 470 x 145 mm (18.5 x 5.9 inches)
	QuickMount internal drum	Maximum scan area: 470 x 232 mm (18.5 x 9.1 inches)
<b>Software</b>	ScanXact	
	Dot4Dot - Scanning of screened film separations (optional)	
<b>Platform (required)</b>	G3 or G4 Mac	
<b>Platform (minimum specs.)</b>	256MB RAM - 1GB hard disk - 24 bit display	
<b>Platform (recommended specs.)</b>	512MB RAM - 40GB hard disk - 24 bit display	
<b>Dimensions</b>	755 x 585 x 1150 mm high (29.0 x 23.0 x 45.3 inches high)	
<b>Weight</b>	115 kg (252 lbs)	
<b>Electrical supply</b>	100-127V, 200-240V autoranging - 50/60 Hz - 0.3kVA	
<b>Climate</b>	Operating temperature 15° to 35°C (59° to 95° F) - Relative humidity 50% to 65% non-condensing	

**Note: please specify your power requirements with your order.**

## KEY FEATURES

- 12000 dpi optical quality resolution.
- Background scanning for maximum productivity
- Choice of 3 interchangeable drums: External, SlickMount or SlickMount
- Precision triple photomultiplier scanner
- ScanXact Software
- CopyDot software available



### Itek Colour Graphics Ltd. (ICG®)

The Old Drawing Office,  
50 High Street, Kingswood,  
Bristol, BS15 4AJ, UK.  
Tel: +44 (0) 117 980 5978  
Fax: +44 (0) 117 960 3282  
Email: sales@icgscanners.com

**Web: [www.icgscanners.com](http://www.icgscanners.com)**